

Phone: (02) 6341 1744 Fax: (02) 6341 1200

Email: sales@ellisandsonsgroup.com.au

8-10 Bourke St COWRA NSW 2794

PLEASE INDICATE

☐ CONFIRMED ORDER

 $\ \square$ QUOTE ONLY

HOOD TARP COMPLETE KIT MEASUREMENT FORM

Customer: Address:	Da Pho			
	Fax			
Contact:	Order/Rego No:	Email:		
HOOD TYPE	COLOUR SELECTION	BOW SELECTION	BOW SELECTION	
☐ 60 % Quarry Spec	(Circle one of the Following)			
□ Mesh				
□ PVC	Mesh: Black, Maroon, Green, Red,	0 0	F	
☐ 80 % Waterproof –PVC	Light/Dark Blue, Terracotta, Grey,	Quarry Bows 150 mm	Excavation Bows	
\square Roll up flap with ropes and	HiVis Orange*, HiVis Green*	□ 350 mm	□ 350 mm□ 450 mm	
rubber rings	*Surcharge Applies	□ 450 mm	□ 450 mm	
☐ Asphalt Spec – Canvas (Black)	Suicharge Applies	□ 500 mm	□ 300 mm*	
BODY TYPE	PVC: Black, Red, White, Grey, Blue, *(Narrow Body 1900 – 2			
☐ Rigid Truck	Maroon, Green, Yellow	(,	
□ Dog Trailer	a. con, c. con, concu			
□ Semi	OPERATING REQUIREMENTS	ELECTRIC	ELECTRIC SYSTEM	
Brand of Body:	☐ Belt Handle Drive (Shaft System)	□ 12 Vol	☐ 12 Volt	
TAILGATE	*side height (G) required for correct belt si	.* □ 24 Volt		
☐ Two Way Gate	☐ Chain Handle Drive (Shaft System)	☐ Not Required		
☐ Forward Hinged	☐ Cable Handle Drive (Not a Shaft System		•	
☐ Rear Top Hinged	Note: Please use other forms provided for			
☐ Other:				
	r un vouterproof unu/or r un out rurp syst			
REQUIRED DIMENSIONS		1		
A Inner Width Front				
B Inner Width Rear				
C Outer Width Front			M	
D Outer Width Rear	_ / `			
E Total Length			Z	
	<u> </u>	C 45	K +X	
F Front of Body to Hinge		A .	> >	
G Side Height				

Required Tarp Length (From Front of Bin) *Note all tarps are custom made to fit the provided

measurements, therefore their accuracy is your

responsibility. If you have any questions regarding this form, please contact our head office.

Hoist Height above rail Rear Post Width Hoist Width at rail

K Hoist Depth at rail L Hoist Top Width M Hoist Top Depth N Headboard Height

> Please draw any additional details that may be required on the figure.

O